

TECHNICAL GUIDANCE

General Installation Guidance

Taylormade Facades Ltd — Architectural Mouldings, Est. 2003

This guide summarises general fixing principles across our standard profile ranges. It is **not project-specific** — always refer to your project architect's details and the relevant product data sheet before installation. For guidance on a specific project, contact our technical team.

Cornices

C001 · C002

Lengths: 800mm & 1200mm standard (specialist lengths on request) **Tolerance:** +/- 2mm

- Taylormade Facades pre-coated profile fully bed bonded with Polymer Basecoat.
- Render or facing brick as per project specification (by others).

Parapet Cappings

PC001 · PC002 · PC003 · PC004

Lengths: 800mm & 1200mm standard (specialist lengths on request) **Tolerance:** +/- 2mm

- Taylormade Facades pre-coated profile fully bed bonded with Polymer Basecoat.
- Also refer to the Taylormade parapet application details for full weatherproofing requirements.
- Render or facing brick as per project specification (by others).

Garden Wall Copings

GWC001 · GWC002

Lengths: 800mm & 1200mm standard (specialist lengths on request) **Tolerance:** +/- 2mm

- Taylormade Facades pre-coated profile fully bed bonded with Polymer Basecoat.
- Render as per project specification (by others).

Window Cills

WC001A/B · WC002A/B · WC003A/B · SMC001A/B · SMC002A/B

Sizes: 17 sizes, 460mm–2260mm window openings **Tolerance:** +/- 2mm

- Sealant between the window cill and window profile (by others).
- Cill fully bed bonded with Taylormade Facades pre-coated profile and Polymer Basecoat.
- Optional cill stooling to suit window surround detail — state at time of ordering if stools are not required.
- Render or facing brick as per project specification (by others).

Window Heads

WH001A/B · WH002A/B

Sizes: 17 sizes, 460mm–2260mm window openings **Tolerance:** +/- 2mm

- **Rendered:** Parex render as per project specification, with Taylormade Facades pre-coated profile fully bed bonded with Polymer Basecoat.
- **Facing brickwork:** facing brick as per project specification (by others) — brickwork thickness reduced to suit the profile (by others).
- Can be combined with a keystone — specify at time of ordering.

Keystones

KS001 · KS002

Use: Combines with either window head range **Tolerance:** +/- 2mm

- Positioned centrally over the window head — specify keystone additions when placing an order.
- **Rendered:** Taylormade Facades pre-coated profile fully bed bonded with Parex Maite.
- **Facing brickwork:** Taylormade Facades pre-coated profile fully bed bonded with Polymer Basecoat, with brickwork or blockwork thickness reduced to suit the profile (by others).

String Bands

SB001 · SB002 · SB003 · SB004 · SB005 · SB006

Lengths: 800mm & 1200mm standard (specialist lengths on request) **Tolerance:** +/- 2mm

- Taylormade Facades pre-coated profile fully bed bonded with Polymer Basecoat.
- Render or facing brick as per project specification (by others).

Quoin Stones

QS001A/B · QS002A/B · QS003A/B

Height: 215mm (matches standard brick coursing) **Tolerance:** +/- 2mm

- Facing brick layout should be coursed to match the joints of the quoins.
- Taylormade Facades pre-coated profile fully bed bonded with Polymer Basecoat.

General Notes — All Profile Ranges

- All profiles are finished with Taylormade Facades Polymer Basecoat prior to render or facing application.
- Fixing method varies by profile type and project substrate — always refer to the specific product data sheet for the profile being installed.
- This guidance is general information only and is not project-specific. Always refer to your project architect's details and the specific product data sheet before installation.
- Bespoke or non-standard profiles are engineered individually — contact our technical team for fixing guidance specific to your drawing.

Taylormade Facades Ltd

Gasworks Road, Aberaman, Aberdare, CF44 6RS, Wales, UK

01685 875410 · info@taylormadefacades.com · taylormadefacades.com